

Series 8, island cooker hood, 90 cm, Stainless steel DIB091U51B



DHZ1231	Adapter for roof inclination left/right
DHZ1241	Adapter for roof inclination front/back
DHZ1246	Chimney extension 1100 mm
DHZ1251	Extension for mounting kit 500 mm
DHZ1253	Extension for mounting kit 1000 mm
DHZ5385	Standard recirculation kit
DSZ5201	CleanAir active carbon filter spare part
DSZ6230	CleanAir Recirculation Kit
DHZ1256	Chimney extension 1600 mm
DHZ5346	Standard odor filter (replacement)
DZZ0XX0P0	Long Life odor filter (replacement)

The island chimney hood: the perfect solution for your cooking island thanks to flexible ceiling mounting.

- **especially silent:** maximal extractor performance with minimal noise
- **Easy-to-clean interior:** hidden screws and cables along with rounded edges make cleaning easy.
- **EcoSilence Drive:** our highly efficient motor saves on energy, not on performance.
- **Intensive speed setting:** removes strong kitchen odours especially quickly and effectively.

Typology:Island/Ceiling
 Length electrical supply cord: 130.0 cm
 Height of the chimney: 698-878/698-998 mm
 Height of product, without chimney: 46 mm
 Net weight: 28.3 kg
 Type of control:Electronic
 Number of speed settings:3-stage + 2 intensive
 Max. air extraction: 620 m³/h
 Boost position output recirculating: 480.0 m³/h
 Max. air recirculation: 400 m³/h
 Boost position air extraction: 1000 m³/h
 Number of lights: 4
 Noise level:60 dB(A) re 1pW
 Diameter of air outlet: 120 / 150 mm
 Grease filter material:Washable aluminium
 Odour filter: No
 Operating Mode:Convertible
 Optional accessories: DHZ1231, DHZ1241, DHZ1246, DHZ1251,
 DHZ1253, DHZ5385, DSZ5201, DSZ6230, DHZ1256, DHZ5346,
 DZZ0XX0P0
 Type of lamps used: LED
 Total power of the lamps: 12 W
 Grease filter type:Kassette
 Connection rating: 272 W
 Fuse protection:10 A
 Voltage: 220-240 V
 Frequency: 50; 60 Hz
 Plug type:GB plug
 Installation typology: Island
 Material body: Stainless steel
 Plug type:GB plug
 Dimensions of the product, with chimney (if exists) (in):x x
 Dimensions of the packed product: 32.87 x 24.01 x 40.74
 Net weight:62.000 lbs
 Gross weight: 82.000 lbs
 Motor location: Integrated motor in hood chimney
 No-return airflow flap: No
 Length electrical supply cord: 130.0 cm
 Dimensions of the product, with chimney (if exists): 744-1044 x
 900.0 x 600.0 mm
 Dimensions of the packed product (HxWxD): ... 835 x 610 x 1035 mm
 Net weight: 28.3 kg
 Gross weight: 37.0 kg



4 242002 779584

**Series 8, island cooker hood, 90 cm,
Stainless steel
DIB091U51B**

**The island chimney hood: the perfect
solution for your cooking island thanks to
flexible ceiling mounting.**

-
- Island chimney hood
 - 900 mm width
 - Ceiling mounted hood
 - Suitable for ducted or re-circulated extraction
 - For recirculated extraction or CleanAir recirculation kit (accessory) needed
 - Inner frame
 - air quality sensor
 - Push button controls with digital display
 - Electronic via Push button controls with digital display
 - 1-9 min.
 - Twin channel high performance fan motor
 - Light dimmer function
 - SoftLight, Light dimmer function
 - Metal grease filter, dishwasher safe
 - grease- and charcoal filter
 - Extraction rate according to DIN/EN 61591 ø 15 cm: max. Normal 620 m³/h Intensive 1000 m³/h
 - Extraction rate exhaust air according to EN 61591:
 - max. normal use 620 m³/h, intensive 1000 m³/h
 - 1000EE
 - Noise level according to EN 60704-3 und EN 60704-2-13 exhaust air:
 - Max. normal use: 60 dB(A) re 1 pW (46 dB(A) re 20 µPa sound pressure)
 - Intensive: 60 dB(A) re 1 pW (57 dB(A) re 20 µPa sound pressure)
 - Additional noise insulation
 - Dimensions exhaust air (HxWxD): 744-924 x 900 x 600 mm
 - Dimensions recirculating (HxWxD): 744-1044 x 900 x 600 mm
 - Dimensions recirculating with CleanAir module (HxWxD): 812-1044 x 900 x 600 mm
 - Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
 - Power rating: 272 W

**Series 8, island cooker hood, 90 cm,
Stainless steel
DIB091U51B**

