

## Series 2, free-standing fridge-freezer with freezer at bottom, 186 x 60 cm, Stainless steel look KGN36NL30M











### The NoFrost bottomfreezer with MultiBox: Has enough room for all your food

- LED light: illuminates the refrigerator evenly without glare, lasts for the life of the appliance.
- MultiAirflow System provides even air distribution in the fridge for prolonged freshness.
- SuperFreezing: Protects frozen food from defrosting.
- Perfect Fit: The appliance can be positioned right next to side walls and furniture flexible installation possible
- Alarm: Warning signal when the door is not closed or other error happens

Built-in / Free-standing:	-
Number of compressors:	
Number of independent cooling systems:	
Width of the appliance:	
Height:	
Depth of the product:	
Net weight:	-
Door panel options:	
Door hinge:	•
Number of Adjustable Shelves in fridge compar	
Shelves for Bottles:	
Frost free system:	
Interior ventilator:	
Reversible Door Hinge:	
Length electrical supply cord:	
Noise level:	` ' '
Multi-Flow Air Tower:	
Fast cooling switch:	No
Fast freezing switch:	
Temperature Controlled Drawer:	No
Humidity Control Drawer:	No
Number of Door Bins - Refrigerator:	4
Door bin adjustability - Refrigerator:	No
Tilt-out door bins in fridge:	No
Gallon Storage:	Yes
Number of Gallon storage:	1
Motorized Shelf:	
Material ofthe shelves:	Safety glass
Door opened indicator freezer:	No
Automatic motor-driven ice-maker:	No
Connection rating:	100 W
Fuse protection:	10 A
Voltage:	220-240 V
Frequency:	50 Hz
Freezing capacity:	11 kg
Storage Period in Event of Power Failure (h):	12 h
Door panel options:	Not possible
Noise level:	42 dB(A) re 1pW
Energy Star Qualified:	No
Plug type:	GB plug
Required cutout/niche size for installation (in):	X
Dimensions of the packed product:	75.78 x 25.62 x 30.35
Net weight:	135.000 lbs
Gross weight:	149.000 lbs





# Series 2, free-standing fridge-freezer with freezer at bottom, 186 x 60 cm, Stainless steel look KGN36NL30M

consumption.

Environment and Safety

Dimension and installation

Main Features

### The NoFrost bottomfreezer with MultiBox: Has enough room for all your food

#### Performance and consumption

- Total capacity: 329 litres
- Airborne acoustical noise emissions: 42 dB dB(A) re 1 pW

#### Design

- Door Stainless steel look, side panels Pearl Grey
- integrated horizontal handle
- LED with Soft Start in fridge section

#### **Comfort and Safety**

- NoFrost
- LED electronic control
- Super freezing with automatic switch off

#### **Fridge Section**

- Capacity refrigeration zone:219 litres
- Multi Airflow-System
- 4 safety glass shelves of which 3 are height adjustable
- 4 door bins

#### Freshness System

- MultiBox: transparent drawer with wave bottom, ideal for the storage of fruits and vegetables

### Freezer Section

- Freezer capacity: 110 litres
- Freezing capacity: 11 kg in 24 hours
- Storage time in power failure: 15 Hours
- 3 transparent freezer drawers
- Freezing calendar

#### Dimensions

- Dimensions: H 186 cm x L 60 cm x D 66 cm

#### Technical Information

- Door right hinged, reversible Door
- Height adjustable front feet, roles in the back
- Climate Class SN-T
- Connection load: 100 W
- Rated Voltage 220 240 V


#### Accessories


#### **Country Specific Options**


- Gross capacity, total: 329 l
- Gross capacity cooling 219 l
- Gross capacity\*\*\*\* freezer: 110 l (-18°C and below)
- Based on the results of the standard 25-hour test. Actual consumption depends on usage/position of the appliance.
- To achieve the declared energy consumption, the attached distanceholders have to be used. As a result, the appliance depth increases by about 3.5 cm. The appliance used without the distance holder is fully functional, but has a slightly higher energy



## Series 2, free-standing fridge-freezer with freezer at bottom, 186 x 60 cm, Stainless steel look KGN36NL30M







Appliance name	Α	В	С	D
KGN33, 36, 39, 46, 49	0/65	20	590	125
KGF39, 49	0/65	20	590	125

#### Dimension A:

In models with vertical integrated handles, in order to open easily, a minimum distance of 65 mm is needed.

measurements in mm